

# MEDIABOX SPECS



Compatible Camcorders	Which with 1394 interface	Sony, Panasonic, Canon, JVC Camcorders which with IEEE-1394 (format including: DVSD, DVCAM, HDV, DVCpro25, DVCpro50)
	With stimulated port	Camcorders with simulated composite port
Input/output port	Connect with camcorders	IEEE-1394 port Simulated video input port: DB15 (composite video port) Simulated audio port: DB15(unbalanced stereo audio port)
	Connect with computers	USB2.0 port (driver free)
	A/V signal output port	DB15 (composite video port, unbalanced stereo audio port), earphone port
Supported format		AVI2, Matrox AVI, WAV, MP3 (only for HDV audio)
Supported coding format		Encode: MPEG4+incompressible audio (WAV) Decode: DVSD, DVCAM, MPEG4+incompressible audio (WAV)
Supported recorder file format		DVSD, DVCAM, DVCPRO, DVCPRO50
Hard disk		Support big capacity hard disk: 40G/80G/120G/160G and more, Hard disk is changeable
File management		According to date/time for numbering the files. Be able to delete files
Play		Play on internal LCD panel or external monitor
Control method		Mediabox panel control or camcorder control
Operation		Collection, recording, editing, playing, USB disk, file delete and format disk. Etc.
Power		Power consume less than 7W With high capacity Li-ion battery (7.4V), normally can work for around 4 hrs Battery is changeable With power supply, Mediabox can charge the battery when it is working. The charging time is around 3.5hr

Measurement and weight	Measurement: 155mmX103mmX39mm Weight: 800g
Humidity and temperature	Operate temperature: 0°C~40°C (32°F~104°F) Operate humidity: 30%~90% RH Non-working state temperature: -20°C~60°C (-40°F~140°F) Non-working humidity: less than 85% RH
Anti-shock ability	When collecting data, with continuously vibration, (if it is DVCpro50, continuously vibration 5 sec. or if it is DVCpro25/DVSD/DVCAM, continuously vibration 10sec.) the data will not lose (vibration range: 10cm, frequency: 1~2time/sec)

	Format	Record time (160G Hard Disk)	Editing/compose	Playback on Mediabox
collection	DVSD	12 hours	support	support
	DVCAM	12 hours	support	support
	HDV	12 hours	Don't support	Don't support
	DVCPRO25	12 hours	Don't support	Don't support
	DVCPRO50	6 hours	Don't support	Don't support
record	MPEG4	30 hours	support	support

Manufacturer	Type	Model	MEDIABOX collection
SONY	DV (Mini DV)	DCR-PC55E,DCR-HC90E,DCR-HC43E,DCR-HC21E/33E,DCR-VX2100E	support
	DVCAM	DSR-250P/1,DSR-PDX10P,HVR-A1C,HVR-Z1C,DSR-570WSP,DSR-300p/370P/390P,DSR-250P,DSR-PD150P,DSR-PD170,DSR-PD190P,DSR-PD100AP,DSR-600PL,DSR-650WSPL	support
PANASONIC	DVCpro HD	HVX200,AJ-HPX2100/HPX500	support on DVSD & DVCpro25/50
	DVCpro 50	AJ-D913,AJ-SPX900,AJ-SPC700	support
	DVCpro25	AJ-D615,AJ-D410A	support
	professional DV (25Mbps)	AJ-DVC180A/180B, AJ-DVC33/63	support
CANON	professional DV	XL2,XL1,XM2	support
JVC	professional DV	GY-DV5101EC/ GY-DV5001EC,GY-DV310EC,GY-DV550EC	support